



TECHNICAL SHEET

FA 40 100 10

Designation: Restraint Twisted Rope Lanyard

- Made up of 12mm diam. polyamide twisted rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Spliced end is protected with a strong transparent covering sleeve.
- Colored tracer strand losing color to show that the lanyard is unfit for use.
- Minimum breaking strength : 22 kN.

Compliance : EN354 : 2002.

Length :

Lg : 1 mtr.

Material:

Lanyard: polyamide



HS code

56090090

Carton Size / Pieces

60x40x24 / 50

Unit weight

0,16 kg

AET: N° 2449 Issue 2 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 02/15

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

