



TECHNICAL SHEET

FA 30 101 20

Designation: Energy absorbing twisted rope lanyard

- Energy absorber in 44mm wide webbing which reduces the impact of the fall to less than 6 KN.
- 12mm diam. polyamide twisted rope lanyard.
- Loops protected by an abrasion resistant thimble.
- Spliced end protected with strong covering sleeve.

Connector :

1 steel snap hook opening 17 mm, ref. FA 50 202 17.

Compliance :

EN355 : 2002 and tested as per VG11 - 89/686/CEE

Length :

Lg : 1,8 m (connector included)

Materials :

Lanyard : polyamide

Absorber : polyester and polyamide

Connector : steel



HS code

56090090

Carton size / Pieces

60x40x24 / 25

Unit weight

0,66 kg

AET : N° 4299 Issue 2 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11 : GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



maj : 03/13

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

